



# CoRRect air 26 ALVA



## Technical Data

- ▶ Complies with the DGUV Information 201-004 (BGI 581)
- ▶ Stainless steel exterior, rust-free
- ▶ Replaceable stainless steel frame with tension locks
- ▶ Smooth, precise, low noise blower
- ▶ Air flow rate 20-120m<sup>3</sup>/h
- ▶ About 8 A power consumption
- ▶ The filter compartment is easy to reach
- ▶ 4-step filtration (Cyclone/G4/H13/carbon filter)
- ▶ Separate installation of cabin air cyclone in low-emission environments
- ▶ Measurements: about 55 x 33 x 34/55 cm (length x width x height/with cyclon)
- ▶ Weight: about 17kg



## Approved throughout Europe

With the CoRRect air 26 ALVA Hauser Umwelt-Service offers a breathing air supply unit that has been proven repeatedly throughout Europe. Thanks to the breadth of experience of our staff and the tried and tested, solid technology, this classic unit ensures the reliable supply of fresh air. With a corresponding sealing of the vehicle cabin it functions in accordance with the german DGUV Information 201-004 (former BGI 581). In the horizontally-mounted bulk carbon filter the division of active carbon remains constant – leakages cannot occur.

Alternatively, we also offer the innovative CoRRect air HLAS high-performance adsorption filter. Long lifetimes help to ensure smooth and efficient operations. The ease of operation and monitoring comes thanks to the CoRRect air C6 comfort control, which boasts numerous standard and optional equipment features.

The capable, experienced team at Hauser Umwelt-Service offers support in all details, including on-site, ensuring that you and your colleagues can breathe healthy air. You will be delighted with the high quality of the CoRRect air 26 ALVA and Hauser Full-Service!

Scope of supply: CoRRect air 26 ALVA incl. mounting frame, cyclone, CoRRect air C6 comfort control, CoRRect air UFA 15 cabin air filter unit.

